



### Case Construction Equipment Wheel Loaders

Specifications	521G	621G*	721G	821G	921G	1021G	1121G
Net peak hp (kW)	131 (98)	162 (121)	179 (133)	211 (158)	242 (180)	296 (221)	320 (239)
Operating weight - lb (kg)	24,122 (10 942)	27,903 (12 657)	32,492 (14 738)	40,057 (18 170)	45,070 (20 443)	55,282 (25 075)	61,650 (27 964)
Full turn tipping load - lb (kg)	15,852 (7 190)	18,943 (8 592)	20,587 (9 338)	24,515 (11 120)	28,529 (12 940)	35,739 (16 211)	38,457 (17 444)
Bucket breakout force - lbf (kg)	19,373 (8 787)	25,488 (11 561)	32,158 (14 587)	35,288 (16 007)	37,688 (17 095)	45,056 (20 437)	49,934 (22 650)
Bucket Size: GP with Bolt-on-edge	2.3 (1.8)	2.75 (2.1)	3.25 (2.5)	4.25 (3.2)	4.75 (3.6)	5.5 (4.2)	6.25 (4.8)
Max material density**	3,446 (2 045)	3,444 (2 044)	3,167 (1 879)	2,884 (1 711)	3,003 (1 782)	3,249 (1 928)	3,077 (1 826)



\*Alternative machine configurations available (i.e., Waste Handler, Commodity King). \*\*ISO 14397-1 Deflected Tires.