



		T7.175 Classic	T7.175 Sidewinder II	T7.190 Classic	T7.190 Sidewinder II	T7.210 Classic	T7.210 Sidewinder II	T7.230 Classic	T7.230 Sidewinder II	T7.245 Classic	T7.245 Sidewinder II	T7.260 Sidewinder II	T7.270 Sidewinder II	T7.290 Sidewinder II	T7.315 Sidewinder II	
<b>Power Command™ Transmission</b>																
Power Command™ full powershift (40 kph)	•	○	○	○	○	○	○	○	○	○	○	○	○	--	--	--
Number of gears / with creeper	(F X R)	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	18 X 6 / 28 X 12	--	--	--
Min. speed / Min. speed with creeper	mph (kph)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	--	--	--
Power Command™ full powershift (40 kph ECO or 50 kph)		○	○	○	○	○	○	○	○	○	○	○	○	--	--	--
Number of gears / with creeper	(F X R)	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	19 X 6 / 29 X 12	--	--	--
Min. speed / Min. speed with creeper	mph (kph)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.2 / 0.2 (1.9 / 0.31)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	1.1 / 0.18 (1.8 / 0.29)	--	--	--
<b>Auto Command™ Transmission</b>																
Auto Command™ continuously variable transmission (40 kph ECO)		--	•	--	•	--	•	--	•	--	•	•	•	•	•	•
Min. speed / Max. speed	mph	--	0.01 / 25 @ 1550 rpm	--	0.01 / 25 @ 1550 rpm	--	0.01 / 25 @ 1550 rpm	--	0.02 / 25 @ 1450 rpm	--	0.02 / 25 @ 1450 rpm	0.02 / 25 @ 1450 rpm	0.02 / 25 @ 1450 rpm	0.02 / 25 @ 1450 rpm	0.02 / 25 @ 1450 rpm	0.02 / 25 @ 1450 rpm
Auto Command™ continuously variable transmission (50 kph ECO)		--	○	--	○	--	○	--	○	--	○	○	○	○	○	○



		T7.175 Classic	T7.175 Sidewinder II	T7.190 Classic	T7.190 Sidewinder II	T7.210 Classic	T7.210 Sidewinder II	T7.230 Classic	T7.230 Sidewinder II	T7.245 Classic	T7.245 Sidewinder II	T7.260 Sidewinder II	T7.270 Sidewinder II	T7.290 Sidewinder II	T7.315 Sidewinder II
Engine speed at 540 / 1000	rpm	1969 / 1924	1969 / 1924	1969 / 1924	1969 / 1924	1969 / 1924	1969 / 1924	1893 / 1950	1893 / 1950	1893 / 1950	1893 / 1950	1893 / 1950	1893 / 1950	--	--
Engine speed at 540E / 1000	rpm	--	--	--	--	--	--	--	1569 / 1893	--	1569 / 1893	1569 / 1893	1569 / 1893	--	--
Engine speed at 1000 / 1000E	rpm	--	--	--	--	--	--	--	1912 / 1583	--	1912 / 1583	1912 / 1583	1912 / 1583	--	--
540 / 540 E / 1000 / 1000E shiftable	rpm	--	--	--	--	--	--	--	--	--	--	--	--	1930 / 1598 / 1853 / 1583	1930 / 1598 / 1853 / 1583
Auto PTO Management		○	●	○	●	○	●	○	●	○	●	●	●	●	●
Front PTO (1000 rpm)	rpm	○	○	○	○	○	○	○	○	○	○	○	○	○	○
<b>Cab</b>															
Comfort Ride™ cab suspension		○	●	○	●	○	●	○	●	○	●	●	●	●	●
Headland Turn Sequence II System (HTS2)		--	●	--	●	--	●	--	●	--	●	●	●	●	●
IntelliView™ IV large screen 10.4" display		--	●	--	●	--	●	--	●	--	●	●	●	●	●
ISO 11783 connector		○	●	○	●	○	●	○	●	○	●	●	●	●	●
IntelliSteer™ auto guidance		○	○	○	○	○	○	○	○	○	○	○	○	○	○
<b>Axles</b>															
4WD front axle		●	●	●	●	●	●	●	●	●	●	●	●	--	--
Suspended front axle		○	○	○	○	○	○	○	○	○	○	○	○	●	●
Supersteer™ front axle		○	○	○	○	○	○	○	○	○	○	○	○	--	--
Steering angle	degrees	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55 / 55 / 65	55	55

