

CR Combine

Specification Element		CR6.80	CR6.90	CR7.90	CR8.90	CR9.90	CR9.90 Elevation	CR10.90
Min. / Max. cutting width grain header	(ft)	20/30	20/35	20/35	24/45	30/45	30/45	30/45
Min. / Max. number of rows corn header		6/8	6/8	6/12	8/16	8/16	8/16	8/16
Monitor options		YES	YES	YES	YES	YES	YES	YES
Optimum cab noise level	(dB(A))	73	73	73	73	73	73	73
Guidance systems		YES	YES	YES	YES	YES	YES	YES
Precision Farming systems		YES	YES	YES	YES	YES	YES	YES
Rotor diameter / length/speed range	(in / in /rpm)	17/104/439-1868	17/104/439-1868	17/104/439-1868	22/104/331-1407	22/104/331-1407	22/104/331-1407	22/104/331-1407
Cleaning: total area under wind control	(in ²)	8370	8370	8370	10075	10075	10075	10075
Cleaning fan		Opti-Fan	Opti-Fan	Opti-Fan	Opti-Fan	Opti-Fan	Opti-Fan	Opti-Fan

Specification Element		CR6.80	CR6.90	CR7.90	CR8.90	CR9.90	CR9.90 Elevation	CR10.90
Grain tank capacity	(bu)	315/326	315/326	315/326/350	410	410	410	410
Unloading speed	(bu/sec)	3.7	3.7	3.7	4	4	4	4
Engine		FPT Cursor 9	FPT Cursor 9	FPT Cursor 9	FPT Cursor 11	FPT Cursor 13	FPT Cursor 13	FPT Cursor 16
Gross engine power	(hp)	333	360	408	469	530	530	598
Max. engine power	(hp)	374	401	449	517	571	571	653
Diesel tank capacity	(gallons)	200	200	200	340	340	340	340
Standard version less header	(lb)	38779	38779	40600	42236	42635	44240	45898
Maximum height	(ft)	13	13	13	13	13	13	13
Maximum width	(ft)	13	13	13	13	13	13	13

