



Skid Steer Loaders

		L213	L216	L221	L218	L220	L228	L234
Engine name / size / number of cylinders	(- / in ³ / -)	N844L / 135.2 / 4	N844LT / 135.2 / 4	F5HFL463*F001 / 207.5 / 4	N844LTA / 135.2 / 4	N844LTA / 135.2 / 4	F5HFL463A / 207.5 / 4	F5BFL413E*B002 / 207.5 / 4
Emissions level		Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final
Gross power	(hp)	49 @ 2800RPM	60 @2800 RPM	74 @2500 RPM	60 @ 2800 RPM	67 @2800 RPM	74 @2500 RPM	90 @ 2500RPM
Rated power	(hp)	46 @2800 RPM	57 @ 2800 RPM	68 @2500 RPM	57 @ 2800 RPM	64 @ 2800 RPM	68 @ 2500 RPM	84 @ 2500 RPM
Maximum torque	(ft-lb)	105.5 @ 1800 RPM	139 @ 1800 RPM	232 @ 1400 RPM	135 @ 1800 RPM	153 @ 1800 RPM	232 @ 1400 RPM	282 @ 1400 RPM
Max Speed	mph	7.4	7.4	11.4	10.8	11.4	10.5	11.5
Operating weight	lb	5070	5510	6970	6230	6470	8245	8900
Standard hydraulic flow	(gallons/minute)	17.5	18.4	24.2	20.6	20.6	24.2	24.2
Average cycle time (raise / dump)	(seconds)	5	5	5.8	4.9	6.1	7.1	7.1
Diesel tank capacity	(gallons)	16	16	19.5	19.5	19.5	25.5	25.5
Height	(in)	17.5	75.5	78.7	77.7	78.7	78.8	80.4
Wheelbase	(in)	37	37	44.4	44.4	44.4	52	52
Ground clearance	(in)	7	7	8	7	7	8	9.5
Width	(in)	59.8	59.8	69.1	66.1	69.1	69.6	76
Lift Type		Radial	Radial	Radial	Vertical	Vertical	Vertical	Vertical
Maximum operating height	(in)	141.1	141.1	154.3	150.4	151.4	159.7	161.3
Dump angle	(°)	40	40	40	52	52	55	48
Tipping Load	(lb)	2600	3200	4200	3600	4000	5600	6800

