

Tractor Loader Backhoes

		B95C	B95C TC	B95C LR	B110C	U80C
Engine name / size / number of cylinders	(- / in ³ / -)	FPT F5HFL413C*A / 207 / 4	FPT F5HFL413B*A / 207 / 4	FPT F5HFL413C*A / 207 / 4	FPT F5HFL413B*A / 207 / 4	FPT F5HFL413D*A / 207 * 4
Emissions level		Tier 4A	Tier 4A	Tier 4A	Tier 4A	Tier 4A
Gross power	(hp)	97	97	97	110	85
Rated power	(hp)	95	95	95	108	78
Maximum torque	(lb-ft)	334 @ 1400 RPM	334 @ 1400 RPM	334 @ 1400 RPM	339 @ 1400 RPM	276 @ 1500 RPM
Transmission		Power Shuttle (4F/4R) or PowerShift (4F/3R)	Power Shuttle (4F/4R) or PowerShift (4F/3R)	Power Shuttle (4F/4R) or PowerShift (4F/3R)	Power Shuttle (4F/4R) or PowerShift (4F/3R)	Power Shuttle (4F/4R)
Max. speed	(MPH)	23.8	23.8	23.8	23.8	24.3
Base Unit Weight	(lb)	16008	18135	16008	16008	-
Maximum hydraulic flow	(gallons/minunte)	40	40	40	40	28.5
Average cycle time (raise / dump)	(seconds)	5.6	5.6	5.6	5.6	-
Diesel tank capacity	(gallons)	35.6	35.6	35.6	35.6	40
Transport Height	(in)	150	150	150	150	108
Wheelbase	(in)	85.6	85.6	85.6	85.6	84
Ground clearance	(in)	15.5	15.5	15.5	15.5	10.9

Width	(in)	90	90	90	90	80
Loader maximum operating height	(in)	168	167	168	170	165
Loader dump angle	(°)	45	45	45	45	45
Loader lift capacity at full height	(lb)	11118	8610	11118	10957	6503
Backhoe maximum operating height	(in)	214	214	221	221	N/A
Backhoe bucket rotation max	(°)	203	203	203	203	N/A
Backhoe maximum dig depth	(in)	174	174	186	186	N/A
Backhoe overall reach	(in)	212	212	223	223	N/A