

### Miller Nitro Front Boom Self-Propelled Sprayers

Miller Nitro Front Boom Self-Propelled Sprayers		5225	5250	6300	6345	6500
Rated power	HP (kw)	275	300 (310 bulge)		320 (345 bulge)	380 (400 bulge)
Transmission / Type		Torq-Trac® hydrostatic drive system with twin Danfoss heavy duty pumps. Manually Controlled.		Torq-Trac® hydrostatic drive system with twin H1 series Danfoss heavy duty pumps. Electronically Controlled.		
Turning Radius - 2 Wheel Steering	ft (m)	13.5' (4.1 m)		15' (4.5 m)		
Turning Radius - Optional 4 Wheel Steering	ft (m)	13.5' (4.1 m)		15' (4.5 m)		
Maximum Ground Clearance	in (cm)	72" (183 cm)	76" (193 cm)			
Tank Capacity	US gal (L)	1000 gal (3785 L)	1000 or 1200 gal (3785 or 4542 L)	1200, 1400, or 1600 gal (4542, 5300, or 6056 L)		
Tank option - 1	Material	Polyethylene		Stainless Steel		
Tank option - 2	Material	Stainless Steel				
Mono-boom Widths	feet (meters)	60, 90/60, 100/60 ft (18, 27/18, 30/18 m)	60, 90/60, 100/60, 120/70 ft (18, 27/18, 30/18, 36/21 m)	90/60, 100/60, 120/70 ft (27/18, 30/18, 36/21 m)		
Truss-boom Widths	feet (meters)	N/A	120/73, 132/73, 135/73 (36/22, 40/22, 41/22 m)			