

Iveco Bus Crossway

	CROSSWAY LINE	CROSSWAY LINE	CROSSWAY LINE	CROSSWAY LINE	CROSSWAY LINE	CROSSWAY LINE
Engine name / size / number of cylinders	Cursor 9 Diesel / 6 cylinders	Cursor 9 Diesel / 6 cylinders	Cursor 9 Diesel / 6 cylinders	Tector 7 Diesel / 6 cylinders	Tector 7 Diesel / 6 cylinders	Tector 7 Diesel / 6 cylinders
Max. torque	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1100 Nm at 1250 - 1600 rpm	1100 Nm at 1250 - 1600 rpm	1100 Nm at 1250 - 1600 rpm
Displacement	8,7 litres	8,7 litres	8,7 litres	6,7 litres	6,7 litres	6,7 litres
Power	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	235 kw (320 hp) at 2500 rpm	235 kw (320 hp) at 2500 rpm	235 kw (320 hp) at 2500 rpm
Length	10 757 mm	12 097 mm	12 962 mm	10 757 mm	12 097 mm	12 962 mm
Width	2 550 mm	3 550 mm	4 550 mm	2 550 mm	3 550 mm	4 550 mm
Height (with/without A/C)	3 460 / 3 370 mm	3 460 / 3 370 mm	3 460 / 3 370 mm	3 460 / 3 370 mm	3 460 / 3 370 mm	3 460 / 3 370 mm
Wheelbase	5 300 mm	6 200 mm	7 065 mm	5 300 mm	6 200 mm	7 065 mm
Front / Rear overhang	2 165 / 3 292	2 605 / 3 292 mm	2 605 / 3 292 mm	2 165 / 3 292	2 605 / 3 292 mm	2 605 / 3 292 mm
Front / Rear track	2068 / 1814	2069 / 1814	2070 / 1814	2071 / 1814	2072 / 1814	2073 / 1814
Internal height	2 280 mm	2 280 mm	2 280 mm	2 280 mm	2 280 mm	2 280 mm
Front / Middle / Rear door access height	344 / 344 mm / -	344 / 344 mm / -	344 / 344 mm / -	344 / 344 mm / -	344 / 344 mm / -	344 / 344 mm / -
Front / Middle / Rear door width	800 mm / 800 mm / -	800 mm / 800 mm / -	800 mm / 800 mm / -	800 mm / 800 mm / -	800 mm / 800 mm / -	800 mm / 800 mm / -
Wall-to-wall turning radius	9 250 mm	10 770 mm	11 900 mm	9 250 mm	10 770 mm	11 900 mm
Kerb-to-kerb turning radius	7 820 mm	8 990 mm	10 120 mm	7 820 mm	8 990 mm	10 120 mm
Approach / departure angles	8,3° / 8°	8,3° / 8°	8,3° / 8°	8,3° / 8°	8,3° / 8°	8,3° / 8°
GVW (max legal permissible weight depending on registration country)	19 000 kg	19 000 kg	19 000 kg	18 000 kg	18 000 kg	18 000 kg
Max. permissible front axle load	7100 kg	7100 kg	7100 kg	7100 kg	7100 kg	7100 kg
Max. permissible middle axle load	-	-	-	-	-	-
Max. permissible rear axle load	12 600 kg	12 600 kg	12 600 kg	12 600 kg	12 600 kg	12 600 kg
Emissions level and homologation	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI

