

Iveco Bus Crossway Low Entry

	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY CITY	CROSSWAY LOW ENTRY LINE	CROSSWAY LOW ENTRY LINE	CROSSWAY LOW ENTRY LINE	CROSSWAY LOW ENTRY LINE	CROSSWAY LOW ENTRY LINE	CROSSWAY LOW ENTRY LINE
<b>Engine name / size / number of cylinders</b>	Cursor 9 Diesel - 6 cylinders	Cursor 9 Diesel - 6 cylinders	Cursor 9 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders	Cursor 9 Diesel - 6 cylinders	Cursor 9 Diesel - 6 cylinders	Cursor 9 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders	Tector 7 Diesel - 6 cylinders
<b>Max. torque</b>	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1100 Nm at 1250 - 1890 rpm	1100 Nm at 1250 - 1890 rpm	1100 Nm at 1250 - 1890 rpm	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1650 Nm at 1200 rpm	1100 Nm at 1250 - 1890 rpm	1100 Nm at 1250 - 1890 rpm	1100 Nm at 1250 - 1890 rpm
<b>Displacement</b>	8,7 litres	8,7 litres	8,7 litres	6,7 litres	6,7 litres	6,7 litres	8,7 litres	8,7 litres	8,7 litres	6,7 litres	6,7 litres	6,7 litres
<b>Power</b>	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	235 kW (320 hp) at 2500 rpm	236 kW (320 hp) at 2500 rpm	237 kW (320 hp) at 2500 rpm	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	265 kW (360 hp) at 2200 rpm	235 kW (320 hp) at 2500 rpm	236 kW (320 hp) at 2500 rpm	237 kW (320 hp) at 2500 rpm
<b>Length</b>	10 845 mm	12 050 mm	12 965 mm	10 845 mm	12 050 mm	12 965 mm	10 845 mm	12 050 mm	12 965 mm	10 845 mm	12 050 mm	12 965 mm
<b>Width</b>	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm	2 550 mm
<b>Height (with/without A/C)</b>	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm	3 230 / 3 140 mm
<b>Wheelbase</b>	4 825 mm	6 030 mm	6 945 mm	4 825 mm	6 030 mm	6 945 mm	4 825 mm	6 030 mm	6 945 mm	4 825 mm	6 030 mm	6 945 mm
<b>Front / Rear overhang</b>	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm	2 725 / 3 295 mm
<b>Front / Rear track</b>	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm	2087 / 1814 mm
<b>Internal height front / rear</b>	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm	2 545 / 1 909 mm
<b>Front / Middle / Rear door access height</b>	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -	320 / 330 mm / -
<b>Front / Middle / Rear door width</b>	1200 mm / 1200 mm / -	1200 mm / 1200 mm / -	1200 mm / 1200 mm / -	1200 mm / 1200 mm / -	1200 mm / 1200 mm / -	1200 mm / 1200 mm / -	800 mm / 1200 mm / -	800 mm / 1200 mm / -	800 mm / 1200 mm / -	800 mm / 1200 mm / -	800 mm / 1200 mm / -	800 mm / 1200 mm / -
<b>Wall-to-wall turning radius</b>	9 140 mm	10 720 mm	11 930 mm	9 140 mm	10 720 mm	11 930 mm	9 140 mm	10 720 mm	11 930 mm	9 140 mm	10 720 mm	11 930 mm
<b>Kerb-to-kerb turning radius</b>	7 300 mm	8 870 mm	10 070 mm	7 300 mm	8 870 mm	10 070 mm	7 300 mm	8 870 mm	10 070 mm	7 300 mm	8 870 mm	10 070 mm
<b>Approach / departure angles</b>	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°	7° / 7°
<b>GVW (max legal permissible weight depending on registration country)</b>	19 000 kg	19 000 kg	19 000 kg	18 000 kg	18 000 kg	18 000 kg	17 900 kg	17 900 kg	17 900 kg	17 900 kg	17 900 kg	17 900 kg
<b>Max. permissible front axle load</b>	7 200 kg	7 200 kg	7 200 kg	7 200 kg	7 200 kg	7 200 kg	6 300 kg	6 300 kg	6 300 kg	6 300 kg	6 300 kg	6 300 kg
<b>Max. permissible middle axle load</b>	-	-	-	-	-	-	-	-	-	-	-	-
<b>Max. permissible rear axle load</b>	12 500 kg	12 500 kg	12 500 kg	12 500 kg	12 500 kg	12 500 kg	11 600 kg	11 600 kg	11 600 kg	11 600 kg	11 600 kg	11 600 kg
<b>Emissions level and homologation</b>	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI	Euro VI