

MAGIRUS MLF FIRE ENGINE



SERVING HEROES. SINCE 1864.

 **MAGIRUS**

MLF FIRE ENGINE TECHNICAL DATA

CONCEPT

/ Chassis	7- to 11-tonne class
/ Cab	1+5
/ Superstructure	AluFire 3 technology
/ Pump capacity	1000 l/min at 10 bar
/ Water tank	600 litres

STANDARD EQUIPMENT

- / Internal water tank for maximum equipment storage capacity
- / Magirus HMI control panel for the easiest possible vehicle operation
- / Variable equipment storage system for individual loading
- / Large area for stowing additional mission-related and/or personal equipment
- / Higher weight reserves for heavier loads / greater amounts of extinguishing agents
- / Continuous ambient lighting for uniform illumination of work site
- / Optimal water tank set-up for balanced weight distribution
- / Ergonomic working conditions due to optimal removal heights – even for heavy equipment

OPTIONALLY AVAILABLE

- / All-wheel drive
- / Water tank for increased volumes of up to 1000 litres
- / 2 breathing apparatuses in cab
- / Pneumatic light mast with halogen, xenon or LED technology
- / LED lighting technology
- / Quick-attack hose reel
- / Rear warning system
- / Extensive additional loading capacity possible
- / Superstructure can be mounted on all suitable chassis in the 7- to 11-tonne class, made by any manufacturer

DETAILED VIEWS



Illustrations may include additional options. We reserve the right to make technical changes or improvements at any time without prior notice. Errors and omissions excepted.

MAGIRUS GmbH • Graf-Arco-Straße 30 • 89079 Ulm
www.magirusgroup.com • magirus@cnhind.com