



Leapmotor C10
Standard Safety Equipment

2024



Adult Occupant



89%

Child Occupant



85%

Vulnerable Road Users



77%

Safety Assist



76%

SPECIFICATION

Tested Model	Leapmotor C10 Style, LHD
Body Type	- 5 door SUV
Year Of Publication	2024
Kerb Weight	1980kg
VIN From Which Rating Applies	- all C10s
Class	Small Family Car

SAFETY EQUIPMENT

	Driver	Passenger	Rear
FRONTAL CRASH PROTECTION			
Frontal airbag	●	●	—
Belt pretensioner	●	●	●
Belt loadlimiter	●	●	●
Knee airbag	✘	✘	—
LATERAL CRASH PROTECTION			
Side head airbag	●	●	●
Side chest airbag	●	●	✘
Side pelvis airbag	●	●	✘
Centre Airbag	●	✘	—

	Driver	Passenger	Rear
CHILD PROTECTION			
Isofix/i-Size	—	✘	●
Integrated CRS	—	✘	✘
Airbag cut-off switch	—	●	—
Child presence detection	—	●	●
SAFETY ASSIST			
Seat Belt Reminder	●	●	●

SAFETY EQUIPMENT (NEXT)

OTHER SYSTEMS	
Active Bonnet	✘
AEB Vulnerable Road Users	●
AEB Pedestrian - Reverse	●
Cyclist Dooring Prevention	●
AEB Motorcyclist	●
AEB Car-to-Car	●
Speed Assistance	●
Lane Assist System	●
Fatigue / Distraction Detection	●

Note: Other equipment may be available on the vehicle but was not considered in the test year.


- Fitted to the vehicle as standard ○ Fitted to the vehicle as part of the safety pack
 ○ Not fitted to the test vehicle but available as option or as part of the safety pack ✘ Not available — Not applicable

 ADULT OCCUPANT

Total 35.9 Pts / 89%


 GOOD  ADEQUATE  MARGINAL  WEAK  POOR

Frontal Impact 13.0 / 16 Pts




Mobile Progressive Deformable Barrier Full Width Rigid Barrier

Lateral Impact 16.0 / 16 Pts



Side Mobile Barrier Side Pole Far-Side Excursion Occupant Interaction

Rear Impact 3.9 / 4 Pts




Rear Seat Front Seat


ADULT OCCUPANT

Total 35.9 Pts / 89%

GOOD
 ADEQUATE
 MARGINAL
 WEAK
 POOR

Rescue and Extrication		3.0 / 4 Pts
Rescue Sheet	Available, ISO compliant	
Advanced eCall	Available	
Multi Collision Brake	Available	
Submergence Check	Compliant	

Comments

The passenger compartment of the Leapmotor C10 remained stable in the frontal offset test. Dummy readings indicated good protection of the knees and femurs for the driver and front passenger. Leapmotor demonstrated that a similar level of protection would be provided to occupants of different sizes and to those sitting in different positions. Analysis of the deceleration of the impact trolley during the test, and analysis of the deformable barrier after the test, revealed that the Leapmotor C10 would be a benign impact partner in a frontal collision. In the full-width rigid barrier test, protection of the driver's chest was marginal but that of all other critical body regions was good or adequate, both for the driver and the rear passenger. In both the side barrier test and the more severe side pole impact, full points were scored, with good protection of all critical body regions. Control of excursion (the extent to which a body is thrown to the other side of the vehicle when it is hit from the far side) was found to be adequate. The Leapmotor C10 has a countermeasure to mitigate against occupant-to-occupant injuries in such impacts. The airbag performed well in Euro NCAP's tests with dummy readings indicating good protection for both the driver and passenger. Tests on the front seats and head restraints demonstrated good protection against whiplash injuries in the event of a rear-end collision. A geometric analysis of the rear seats also indicated good whiplash protection. The car has an advanced eCall system which alerts the emergency services in the event of a crash, and a system to prevent secondary impacts after the car has been in a collision. Leapmotor demonstrated that the doors and windows would be openable to allow occupants to escape in the event of vehicle submergence.

CHILD OCCUPANT

Total 42.0 Pts / 85%


■ GOOD
 ■ ADEQUATE
 ■ MARGINAL
 ■ WEAK
 ■ POOR

Crash Test Performance based on 6 & 10 year old children

24.0 / 24 Pts



16 Pts



8 Pts

Restraint for 6 year old child: *Britax Romer Kidfix i-Size*
 Restraint for 10 year old child: *bebeconfort Manga i-Fix*

Safety Features

6.0 / 13 Pts

	Front Passenger	2nd row outboard	2nd row center
Isofix	✗	●	✗
i-Size	✗	●	✗
Integrated CRS	✗	✗	✗
Top tether	✗	●	✗
Child Presence Detection	●	●	●

● Fitted to test car as standard
 ○ Not on test car but available as option
 ✗ Not available

CRS Installation Check

12.0 / 12 Pts

i-Size	Seat Position				
	Front		2nd row		
			Left	center	Right
	—	—	●	—	●

● Easy
 ● Difficult
 ● Safety critical
 ✗ Not allowed
✗ Airbag ON
 Rearward facing restraint installation not allowed
✗ Airbag OFF

Version 251124

CHILD OCCUPANT

Total 42.0 Pts / 85%

Isofix	Seat Position				
	Front		2nd row		
			Left	center	Right
	—	—	●	—	●
	—	—	●	—	●
	—	—	●	—	●
	—	—	●	—	●
	—	—	●	—	●
	—	—	●	—	●

● Easy
 ● Difficult
 ● Safety critical
 ✘ Not allowed
✘ Airbag ON
 Rearward facing restraint installation not allowed
✘ Airbag OFF

Seatbelt Attached	Seat Position				
	Front		2nd row		
			Left	center	Right
	✘	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	✘	●	●	●	●

● Easy
 ● Difficult
 ● Safety critical
 ✘ Not allowed
✘ Airbag ON
 Rearward facing restraint installation not allowed
✘ Airbag OFF

Version 251124



CHILD OCCUPANT

Total 42.0 Pts / 85%

Comments

In both the frontal offset test and the more severe side pole impact, protection of all critical parts of the body was good for the 6 and 10 year dummy, and the Leapmotor C10 scored maximum points in this part of the assessment. The front passenger airbag can be disabled to allow a rearward-facing child restraint to be used in that seating position. Clear information is provided to the driver regarding the status of the airbag, and the system was rewarded. The C10 is equipped with a direct 'child presence detection' system, which issues a warning when it detects that a child or infant has been left in the car. However, the system did not meet Euro NCAP's requirements and was not rewarded. All of the child restraint types for which the Leapmotor C10 is designed could be properly installed and accommodated in the car.

VULNERABLE ROAD USERS

Total 48.5 Pts / 77%



VRU Impact Protection 24.4 / 36 Pts



Pedestrian & Cyclist Head	10.8 Pts
Pelvis	1.7 Pts
Femur	4.5 Pts
Knee & Tibia	7.4 Pts

VRU Impact Mitigation 24.1 / 27 Pts

System Name	FSC
Type	Auto-Brake with Forward Collision Warning
Operational From	8 km/h

PERFORMANCE | █

AEB Pedestrian 7.0 / 9 Pts

Scenario	Day time	Night time
Car reversing into adult or child	█	—
Adult crossing a road into which a car is turning	█	—
Adult crossing the road	█	█
Child running from behind parked vehicles	█	█
Adult along the roadside	█	█

— Currently not tested

AEB Cyclist 7.8 / 8 Pts

Scenario	Day time
Approaching cyclist crossing from behind parked vehicles	█
Turning across path of an oncoming cyclist	█
Approaching a crossing cyclist	█
Approaching a cyclist along the roadside	█

Version 251124

VULNERABLE ROAD USERS

Total 48.5 Pts / 77%

GOOD
 ADEQUATE
 MARGINAL
 WEAK
 POOR

Cyclist Dooring Prevention 0.3 / 1 Pts

Scenario	Scenario
Dooring a passing cyclist	information, driver door only"

AEB Motorcyclist 6.0 / 6 Pts

Scenario	Autobrake function only	Driver reacts to warning
Approaching a stationary motorcyclist		
Approaching a braking motorcyclist		
Turn across the path of an oncoming motorcyclist		—

— Currently not tested

Lane Support Motorcyclist 3.0 / 3 Pts

Scenario	Day time
Changing lane across the path of an oncoming motorcyclist	
Changing lane across the path of an overtaking motorcyclist	

Comments

Protection of the head of a struck pedestrian or cyclist was predominantly good or adequate, with poor results recorded only on the stiff windscreen pillars. Protection of the pelvis was mixed. Protection of the femur was good at all test locations and that of the knee and tibia was mostly good. The autonomous emergency braking (AEB) system of the Leapmotor can respond to vulnerable road users as well as to other vehicles. The system's response both to pedestrians was good, with adequate protection of pedestrians to the rear of the car. The system's performance in tests of its reaction to cyclists was also good, including marginal protection against 'dooring', where a door is suddenly opened in the path of a cyclist approaching from behind. Performance of the AEB system was good in tests of its response to motorcyclists, scoring full points in this part of the assessment.

SAFETY ASSIST

Total 13.7 Pts / 76%

GOOD
 ADEQUATE
 MARGINAL
 WEAK
 POOR

Speed Assistance 2.2 / 3 Pts

System Name	Map and Camera
Speed Limit Information Function	Camera & Map, subsigns supported
Speed Limitation Function	Intelligent ACC (accurate to 5km/h)

Occupant Status Monitoring 1.6 / 3 Pts

> Seatbelt Reminder 1.0 / 1 Pts

Applies To	Front and rear seats		
	Driver Seat	Front Passenger(s)	Rear Passenger(s)
Warning			
Visual	●	●	●
Audible	●	●	●
Occupant Detection	—	●	●

● Pass ● Fail — Not available

> Driver Monitoring 0.6 / 2 Pts

System Name	Driver Monitoring System
Type	Direct eye monitoring
Operational From	10 km/h
Fatigue	Sleep
Distraction	Long & Short Distraction and Phone Use

SAFETY ASSIST

Total 13.7 Pts / 76%

Lane Support

2.8 / 3 Pts

System Name	FSC+BSD
Type	LKA and ELK
Operational From	60 km/h
PERFORMANCE	
Emergency Lane Keeping	GOOD
Lane Keep Assist	GOOD
Human Machine Interface	GOOD

AEB Car-to-Car

7.3 / 9 Pts

System Name	FSC
Type	Autonomous emergency braking and forward collision warning
Operational From	8 km/h
Sensor Used	camera

Scenario	Autobrake function only	Driver reacts to warning
Approaching a car crossing a junction		
Approaching a car head-on		—
Turning across the path of an oncoming car		—
Approaching a stationary car		
Approaching a slower moving car		—
Approaching a braking car		—

— Currently not tested



SAFETY ASSIST

Total 13.7 Pts / 76%

Comments

Overall, the performance of the autonomous emergency braking (AEB) system was good in tests of its reaction to other vehicles, with impacts being avoided in most tests. A seatbelt reminder system is fitted as standard to the front and rear seats. The car has a direct driver status monitoring system as standard, detecting driver fatigue and several types of distraction. The lane support system gently corrects the vehicle's path if it is drifting out of lane and also intervenes in some more critical situations. The speed assistance system identifies the local speed limit. The driver can choose to allow the limiter to be set automatically by the system.

RATING VALIDITY

Variants of Model Range

Body Type	Engine	Model Name/Code	Drivetrain	Rating Applies	
				LHD	RHD
5 door SUV	Electric	C10 Style *	4 x 2	✓	✓
5 door SUV	Electric	C10 Design	4 x 2	✓	✓

* Tested variant

Annual Reviews and Facelifts

Date	Event	Outcome
December 2024	Rating Published	2024 ★★★★★ ✓