



GEELY EX5
Standard Safety Equipment

2025



Adult Occupant



86%

Child Occupant



87%

Vulnerable Road Users



83%

Safety Assist



83%

SPECIFICATION

Tested Model	GEELY EX5 Pro, LHD
Body Type	- 5 door SUV
Year Of Publication	2025
Kerb Weight	1715kg
VIN From Which Rating Applies	- all GEELY EX5s
Class	Small SUV

SAFETY EQUIPMENT

	Driver	Passenger	Rear
FRONTAL CRASH PROTECTION			
Frontal airbag	●	●	—
Belt pretensioner	●	●	●
Belt loadlimiter	●	●	●
Knee airbag	✗	✗	—
LATERAL CRASH PROTECTION			
Side head airbag	●	●	●
Side chest airbag	●	●	✗
Side pelvis airbag	●	●	✗
Centre Airbag	●	✗	—

	Driver	Passenger	Rear
CHILD PROTECTION			
Isofix/i-Size	—	●	●
Integrated CRS	—	✗	✗
Airbag cut-off switch	—	●	—
Child presence detection	—	✗	●
SAFETY ASSIST			
Seat Belt Reminder	●	●	●

SAFETY EQUIPMENT (NEXT)

OTHER SYSTEMS		
Active Bonnet		✖
AEB Vulnerable Road Users		●
AEB Pedestrian - Reverse		●
Cyclist Dooring Prevention		●
AEB Motorcyclist		●
AEB Car-to-Car		●
Speed Assistance		●
Lane Assist System		●
Fatigue / Distraction Detection		●

Note: Other equipment may be available on the vehicle but was not considered in the test year.

- Fitted to the vehicle as standard
- Fitted to the vehicle as part of the safety pack
- Not fitted to the test vehicle but available as option or as part of the safety pack
- ✖ Not available
- Not applicable

 ADULT OCCUPANT

Total 34.5 Pts / 86%

GOOD ADEQUATE MARGINAL WEAK POOR

Frontal Impact

12.3 / 16 Pts



Mobile Progressive Deformable Barrier



Full Width Rigid Barrier

Lateral Impact

15.6 / 16 Pts



Side Mobile Barrier



Side Pole



Far-Side Excursion



Occupant Interaction

Rear Impact

4.0 / 4 Pts



Rear Seat



Front Seat

 ADULT OCCUPANT

Total 34.5 Pts / 86%

GOOD

ADEQUATE

MARGINAL

WEAK

POOR

Rescue and Extrication		2.7 / 4 Pts
Rescue Sheet	Available, ISO compliant	
Advanced eCall	Available	
Multi Collision Brake	Available	
Submergence Check	Compliant	

Comments

In the frontal offset test of the GEELY EX5, several welds around the base of the A-pillar became detached, and there was some tearing of the metal. GEELY showed that the structure did not incur significantly greater damage in a more severe test, but a penalty was applied to the score. Dummy readings indicated good protection of the knees and femurs of both front seat occupants. Owing to the bodyshell damage, GEELY were precluded from demonstrating a similar level of protection would be provided to occupants of different sizes and to those sitting in different positions. Analysis of the deceleration of the impact trolley during the test, and analysis of the deformable barrier after the test, revealed that the GEELY EX5 would be a moderately benign impact partner in a frontal collision. In the full-width rigid barrier test, protection of the rear passenger's chest was rated as weak, based on dummy readings of compression. In both the side barrier test and the more severe side pole impact, good or adequate protection was provided to all critical parts of the body. Control of excursion (the extent to which a body is thrown to the other side of the vehicle when it is hit from the far side) was found to be good. The GEELY EX5 has a countermeasure to mitigate against occupant-to-occupant injuries in such impacts. The airbag performed well in Euro NCAP's tests with dummy readings indicating good protection for both the driver and passenger. Tests on the front seats and head restraints demonstrated good protection against whiplash injuries in the event of a rear-end collision. A geometric analysis of the rear seats also indicated good whiplash protection. The car has an advanced eCall system which alerts the emergency services in the event of a crash, and a system to prevent secondary impacts after the car has been in a collision. GEELY demonstrated that the doors and windows would be openable to allow occupants to escape in the event of vehicle submergence.

 CHILD OCCUPANT

Total 43.0 Pts / 87%

GOOD ADEQUATE MARGINAL WEAK POOR

Crash Test Performance based on 6 & 10 year old children 24.0 / 24 Pts

Frontal Impact16 Pts



Lateral Impact8 Pts



Restraint for 6 year old child: *Cybex Solution T i-Fix*
Restraint for 10 year old child: *Osann Boost*

Safety Features 7.0 / 13 Pts

	Front Passenger	2nd row outboard	2nd row center
Isofix	●	●	✗
i-Size	●	●	✗
Integrated CRS	✗	✗	✗
Top tether	●	●	✗
Child Presence Detection	✗	●	●

● Fitted to test car as standard ○ Not on test car but available as option ✗ Not available

CRS Installation Check 12.0 / 12 Pts

 i-Size	Seat Position				
	Front		2nd row		
			Left	center	Right
	●	●	●	—	●

● Easy ● Difficult ● Safety critical ✗ Not allowed
 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF

 CHILD OCCUPANT

Total 43.0 Pts / 87%

 Isofix	Seat Position				
	Front		2nd row		
			Left	center	Right
	●	●	●	—	●
	✗	●	●	—	●
	●	●	●	—	●
	●	●	●	—	●
	●	●	●	—	●
	✗	●	●	—	●

● Easy ● Difficult ● Safety critical ✗ Not allowed

 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF

Seatbelt Attached	Seat Position				
	Front		2nd row		
			Left	center	Right
	✗	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	●	●	●	●	●
	✗	●	●	●	●

● Easy ● Difficult ● Safety critical ✗ Not allowed

 Airbag ON Rearward facing restraint installation not allowed  Airbag OFF

 CHILD OCCUPANT

Total 43.0 Pts / 87%

Comments

In both the frontal offset test and the side barrier test, protection of all critical parts of the body was good or adequate for the 6 and 10 year dummy. The front passenger airbag can be disabled to allow a rearward-facing child restraint to be used in that seating position. Clear information is provided to the driver regarding the status of the airbag and the system was rewarded. The EX5 is equipped as standard with 'child presence detection', a system which issues a warning when it recognises that a child or infant may have been left in the car. However, the system did not meet Euro NCAP's requirements and was not rewarded. All of the child restraint types for which the GEELY EX5 is designed could be properly installed and accommodated in the car.

 VULNERABLE ROAD USERS

Total 52.8 Pts / 83%

GOOD

ADEQUATE

MARGINAL

WEAK

POOR

VRU Impact Protection 29.3 / 36 Pts



Pedestrian & Cyclist Head	13.2 Pts
Pelvis	3.3 Pts
Femur	3.9 Pts
Knee & Tibia	8.9 Pts

VRU Impact Mitigation 23.4 / 27 Pts

System Name	Collision Mitigation Support Front
Type	Auto-Brake with Forward Collision Warning
Operational From	4 km/h
PERFORMANCE	

AEB Pedestrian 6.6 / 9 Pts

Scenario	Day time	Night time
Car reversing into adult or child		—
Adult crossing a road into which a car is turning		—
Adult crossing the road		
Child running from behind parked vehicles		
Adult along the roadside		

— Currently not tested

AEB Cyclist 7.8 / 8 Pts

Scenario	Day time
Approaching cyclist crossing from behind parked vehicles	
Turning across path of an oncoming cyclist	
Approaching a crossing cyclist	
Approaching a cyclist along the roadside	



VULNERABLE ROAD USERS

Total 52.8 Pts / 83%



GOOD



ADEQUATE



MARGINAL



WEAK



POOR

Cyclist Dooring Prevention



0.0 / 1 Pts

Scenario	
Dooring a passing cyclist	

AEB Motorcyclist



6.0 / 6 Pts

Scenario	Autobrake function only	Driver reacts to warning
Approaching a stationary motorcyclist		
Approaching a braking motorcyclist		
Turn across the path of an oncoming motorcyclist		—

— Currently not tested

Lane Support Motorcyclist



3.0 / 3 Pts

Scenario	Day time
Changing lane across the path of an oncoming motorcyclist	
Changing lane across the path of an overtaking motorcyclist	

Comments

Protection of the head of a struck pedestrian or cyclist was largely good or adequate, with poor results recorded on the stiff windscreen pillars. Protection of the pelvis and that of the femur was mixed, while protection of the knee and femur was mostly good. The autonomous emergency braking (AEB) system of the GEELY can respond to vulnerable road users as well as to other vehicles. The system's response to pedestrians was good, but protection of those to the rear of the car is poor. The system's performance in tests of its reaction to cyclists was also good but protection against 'dooring', where a door is suddenly opened in the path of a cyclist approaching from behind, scored no points. Performance of the AEB system was good in tests of its response to motorcyclists, with maximum points being scored.

 SAFETY ASSIST

Total 15.1 Pts / 83%

GOOD ADEQUATE MARGINAL WEAK POOR

Speed Assistance 2.2 / 3 Pts

System Name	Speed Assistance System
Speed Limit Information Function	Camera & Map, subsigns supported
Speed Limitation Function	Intelligent ACC (accurate to 5km/h)

Occupant Status Monitoring 2.5 / 3 Pts

> Seatbelt Reminder 1.0 / 1 Pts

Applies To	Front and rear seats		
Warning	Driver Seat	Front Passenger(s)	Rear Passenger(s)
Visual	Pass	Pass	Pass
Audible	Pass	Pass	Pass
Occupant Detection	Not available	Pass	Pass
Pass Fail Not available			

> Driver Monitoring 1.5 / 2 Pts

System Name	Driver Performance Support
Type	Direct eye monitoring
Operational From	10 km/h
Fatigue	Microsleep and Sleep
Distraction	Long & Short Distraction and Phone Use
Impairment	Unresponsive Driver

 SAFETY ASSIST

Total 15.1 Pts / 83%

Lane Support 3.0 / 3 Pts

System Name	Lane Keeping Assist (LKA)
Type	LKA and ELK
Operational From	65 km/h
PERFORMANCE	
Emergency Lane Keeping	 GOOD
Lane Keep Assist	 GOOD
Human Machine Interface	 GOOD

AEB Car-to-Car 7.4 / 9 Pts

System Name	Autonomous Emergency Brake
Type	Autonomous emergency braking and forward collision warning
Operational From	4 km/h
Sensor Used	camera and radar

Scenario	Autobrake function only	Driver reacts to warning
Approaching a car crossing a junction		
Approaching a car head-on		
Turning across the path of an oncoming car		
Approaching a stationary car		
Approaching a slower moving car		
Approaching a braking car		

 Currently not tested



SAFETY ASSIST

Total 15.1 Pts / 83%

Comments

Overall, the performance of the autonomous emergency braking (AEB) system was good in tests of its reaction to other vehicles, with impacts being avoided in most tests. A seatbelt reminder system is fitted as standard to the front and rear seats. The car has a direct driver status monitoring system as standard, detecting driver fatigue and several types of distraction. The lane support system gently corrects the vehicle's path if it is drifting out of lane and also intervenes in some more critical situations. The speed assistance system identifies the local speed limit. The driver can choose to allow the limiter to be set automatically by the system.

RATING VALIDITY



Variants of Model Range

Body Type	Engine	Model Name/Code	Drivetrain	Rating Applies	
				LHD	RHD
5 door SUV	Electric	Pro * Max	4 x 2	✓	✓

* Tested variant

Annual Reviews and Facelifts

Date	Event	Outcome	
April 2025	Rating Published	2025 ★ ★ ★ ★ ★	✓